

ZONE SENTRY SERIES

The Taco Zone Sentry® Zone Valve leads the industry in **ENERGY EFFICIENCY, FLOW CAPACITY (CV), SHUTOFF PRESSURE RATING, SHUTOFF PRESSURE RATING, EASE OF INSTALLATION.**

Primarily designed for use with hot water baseboard, fan coils, radiators, convectors, air handlers, heat pumps and radiant applications.

- UP TO **93% LESS ENERGY USAGE**
- **UNIVERSAL INSTALLATION** ORIENTATION
- **12 VALVES** ON ONE 40VA TRANSFORMER
- MULTI-FUNCTION LED
- **QUICK CONNECT** WIRING
- PUSH BUTTON ACTUATOR REPLACEMENT
- MANUAL OVERRIDE BUTTON
- POSITIONAL INDICATOR
- FULL PORT "BALL VALVE" RESULTING IN HIGHER CV RATINGS COMPARED TO OTHERS
- AVAILABLE SIZES: ½", ¾" & 1" SWT OR PRESS

ADDITIONAL MODELS COVER A WIDE VARIETY OF APPLICATIONS:

- Closed hydronic systems
- Condensing Chilled Water
- Potable Water
- Geo-Sentry: Open or closed loop geothermal systems with water source heat pumps
- Multi-Volt Zone: Hydronic HVAC systems where a quality line voltage zone valve is required.

